

RESINCEM

RESIN FOR MICROCEMENT OR MORTARS

DESCRIPTION

Water-based resin, with excellent compatibility with cement, It is added to different cementitious mixtures, microcement or mortars to consolidate cement layers and improve their mechanical properties, elasticity, adhesion and waterproofing.

RECOMMENDED USES

- Microcement hydraulic binder
- Hydraulic binder for mortars

TECHNICAL CHARACTERISTICS

Appearance	White liquid
Density	1±.04 g /cm ³
Toxicity / flammability	No

APPLICATION

- Use only Resincem to make the mixture. Do not add water.
- The mixing ratio depends on the type of microcement or mortar and the degree of fluidity desired.
- The por-life of the mixture depends on the type of microcement or mortar.

To achieve a homogeneous mixture, it is recommended:

1. Pour the Resincem in a clean container.
2. Add little by little the powder of the microcement or mortar.
3. Blend the mixture with the help of a low revolution professional mixer (300 rpm).
4. Continue adding the powder until the desired fluidity is achieved.
5. If the mixture is too thick add a little Resincem.
6. Stir for at least 4 minutes.
7. Let the mixture rest for 5 minutes.

CENTRAL OFFICE AND FACTORY

C/ Llanterners 44, 961 50 50 24
Pol. Ind. La Figuera info@cemher.com
46970 Alaquas
Valencia (ESPAÑA)

www.cemher.com